

# TopLite™ Series



## MR16 - Triple LED - GU5.3

**Base Type:**

GU5.3

**Color:**

Cool White (6000 K)  
or Warm White (3200 K)

**Intensity:**

270 Lumens

**Input:**

12V AC/DC  
(reversed-polarity protection)

**Output Power:**

3x1W LED

**Led Input Current:**

320mA

**Beam Angle:**

30 or 45 Degrees

**Reflector Efficiency:**

90%

**Body Temperature:**

<60 °C

**LED Working Temperature:**

<75 °C



## MR16 - Triple LED - GU10

**Base Type:**

GU10

**Color:**

Cool White (6000 K)  
or Warm White (3200 K)

**Intensity:**

270 Lumens

**Input:**

110/230V AC/DC  
(reversed-polarity protection)

**Output Power:**

3x1W LED

**Led Input Current:**

320mA

**Beam Angle:**

30 or 45 Degrees

**Reflector Efficiency:**

90%

**Body Temperature:**

<60 °C

**LED Working Temperature:**

<75 °C

No UV or IR Radiation  
Act as direct retrofits to 35W incandescent MR16 lights

Contact Information: [sales@LiteLD.com](mailto:sales@LiteLD.com) / Website: [www.LiteLD.com](http://www.LiteLD.com)

